

CITY OF SPRINGFIELD
BAY COUNTY, FLORIDA
Ordinance No.: 481

FLOOD PREVENTION

AN ORDINANCE OF THE CITY OF SPRINGFIELD, BAY COUNTY, FLORIDA PROVIDING AUTHORIZATIONS, DEFINITIONS, GENERAL PROVISIONS, ADMINISTRATION, FLOOD REDUCTION AND VARIANCE PROCEDURES FOR FLOOD PREVENTION; AND INVALIDATING ORDINANCES IN CONFLICT THEREWITH; AND PROVIDING AN EFFECTIVE DATE.

CONTENTS

Article

ARTICLE 1. STATUTORY AUTHORIZATION. FINDINGS OF FACT. PURPOSE. AND OBJECTIVES

- Section A. Statutory Authorization
- Section B. Findings of Fact
- Section C. Statement of Purpose
- Section D. Objectives
- Section E. Methods of Reducing Flood Losses

ARTICLE 2. DEFINITIONS

ARTICLE 3. GENERAL PROVISIONS

- Section A. Lands to Which This Ordinance Applies
- Section B. Basis for Establishing the Areas of Special Flood Hazard
- Section C. Designation of Flood Damage Prevention Ordinance Administrator
- Section D. Establishment of Development Permit
- Section E. Compliance
- Section F. Abrogation and Greater Restrictions
- Section G. Interpretation
- Section H. Warning and Disclaimer of Liability
- Section I. Penalties for Violation

ARTICLE 4. ADMINISTRATION

- Section A. Permit Procedures
- Section B. Duties and Responsibilities of the Floodplain Management Administrator

ARTICLE 5. PROVISIONS FOR FLOOD HAZARD REDUCTION

- Section A. General Standards
- Section B. Specific Standards
- Section C. Standards for Streams Without Established Base Flood Elevation and Floodways
- Section D. Standards for streams with established base flood elevation without regulatory floodways
- Section E. Standards for AO, AH, and Unnumbered A Zones
- Section F. Standards for Subdivision Proposals
- Section G. Coastal High Hazard Areas
- Section H. Critical Facility

ARTICLE 6. VARIANCE PROCEDURES

- Section A. Designation of Variance and Appeals Board
- Section B. Duties of Variance and Appeals Board
- Section C. Variance Procedures
- Section D. Conditions for Variances
- Section E. Variance Notification
- Section F. Historic Structures
- Section G. Special Conditions
- Section H. No-Impact Certification Within the Floodway

ARTICLE 7. SEVERABILITY

ARTICLE 1. STATUTORY AUTHORIZATION, FINDINGS OF FACT, PURPOSE, AND OBJECTIVES.

SECTION A. STATUTORY AUTHORIZATION.

The Legislature of the State of *Florida* has in *Florida Statutes 166* **authorized and** delegated the responsibility to local government units to adopt regulations designed to promote the public health, safety, and general welfare of its citizenry. Therefore, the *City Commission of the City of Springfield, Bay County, Florida* does hereby adopt the following floodplain management regulations.

SECTION B. FINDINGS OF FACT.

- (1) The flood hazard areas of *the City of Springfield* are subject to periodic inundation, which results in loss of life and property, health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures for flood protection and relief, and impairment of the tax base, all of which adversely affect the public health, safety and general welfare.
- (2) These flood losses are caused by the cumulative effect of obstructions in floodplains causing increases in flood heights and velocities, and by the occupancy in flood hazard areas by uses vulnerable to floods or hazardous to other lands which are inadequately elevated, flood-proofed, or otherwise unprotected from flood damages.

SECTION C. STATEMENT OF PURPOSE.

It is the purpose of this ordinance to promote the public health, safety and general welfare and to minimize public and private losses due to flood conditions in specific areas by provisions designed to:

- (1) Restrict or prohibit uses which are dangerous to **life**, health, safety and property due to water or erosion hazards, which result in damaging increases in erosion or in flood heights and velocities;
- (2) Require that uses vulnerable to floods including facilities which serve such uses be protected against flood damage throughout their intended life span;
- (3) Control the alteration of natural floodplains, stream channels, and natural protective barriers which are involved in the accommodation of flood waters;
- (4) Control filling, grading, dredging and other development which may increase erosion or flood damage; and
- (5) Prevent or regulate the construction of flood barriers which will unnaturally divert floodwaters or which may increase flood hazards to other lands.

SECTION D. OBJECTIVES.

The objectives of this ordinance are:

- (1) To protect human life, and health **and to eliminate or minimize property damage;**
- (2) To minimize expenditure of public money for costly flood control projects;
- (3) To minimize the need for rescue and relief efforts associated with flooding and generally undertaken at the expense of the general public;
- (4) To minimize prolonged business interruptions;

- (5) To minimize damage to public facilities and utilities such as water and gas mains, electric, telephone and sewer lines, roadways, and bridges and culverts located in floodplains;
- (6) To help maintain a stable tax base by providing for the sound use and development of flood prone areas in such a manner as to minimize flood blight areas; and
- (7) To ensure that potential homebuyers are notified that property is in a flood hazard area.

SECTION E. — METHODS OF REDUCING FLOOD LOSSES.

In order to accomplish its purposes, this ordinance includes methods and provisions for:

- ~~(1) Restricting or prohibiting uses which are dangerous to health, safety, and property due to water or erosion hazards, or which result in damaging increases in erosion or in flood heights or velocities;~~
- ~~(2) Requiring that uses vulnerable to floods including facilities which serve such uses be protected against flood damage throughout their intended life span;~~
- ~~(3) Controlling the alteration of natural floodplains, stream channels, and natural protective barriers, which help accommodate or channel flood waters;~~
- ~~(4) Controlling filling, grading, dredging, and other development which may increase flood damage; and~~
- ~~(5) Preventing or regulating the construction of flood barriers that will unnaturally divert flood waters or may increase flood hazards in other areas.~~

ARTICLE 2. DEFINITIONS.

Unless specifically defined below, words or phrases used in this ordinance shall be interpreted so as to give them the meaning they have in common usage and to give this ordinance its most reasonable application.

Accessory structure (Appurtenant structure) means a structure that is located on the same parcel of property as the principal structure and the use of which is incidental to the use of the principal structure. Accessory structures should constitute a minimal investment, may not be used for human habitation, and be designed to have minimal flood damage potential. Examples of accessory structures are detached garages, carports, storage sheds, pole barns, and hay sheds.

Addition (to an existing building) means any walled and roofed expansion to the perimeter of a building in which the addition is connected by a common load-bearing wall other than a firewall. Any walled and roofed addition, which is connected by a firewall or is separated by independent perimeter load-bearing walls, is new construction.

Appeal means a request for a review of the Floodplain Management Administrator's interpretation of any provision of this ordinance or a request for a variance.

Area of shallow flooding means a designated AO or AH Zone on the community's Flood Insurance Rate Map (FIRM) with base flood depths from one to three feet where a clearly defined channel does not exist, where the path of flooding is unpredictable and indeterminate, and where velocity flow may be evident. Such flooding is characterized by ponding or sheet flow.

Area of special flood hazard is the land in the floodplain within a community subject to a one- percent or greater chance of flooding in any given year.

Base flood means the flood having a one percent chance of being equaled or exceeded in any given year (also called the "100-year flood" and the "regulatory flood"). Base flood is the term used throughout this ordinance.

Base Flood Elevation means the highest water-surface elevation associated with the base flood.

Basement means that portion of a building having its floor sub-grade (below ground level) on all sides.

Breakaway wall means a wall that is not part of the structural support of the building and is intended through its design and construction to collapse under specific lateral loading forces without causing damage to the elevated portion of the building or the supporting foundation system.

Building - see Structure.

Coastal high hazard area means an area of special flood hazard extending from offshore to the inland limit of a primary frontal dune along an open coast and any other area subject to high velocity wave action from storms or seismic sources. The area is designated on the FIRM as Zone VI - V30, VE, or V.

Critical facility means a facility for which even a slight chance of flooding might be too great. Critical facilities include, but are not limited to schools, nursing homes, hospitals, police, fire and emergency response installations, installations which produce, use or store hazardous materials or hazardous waste.

Datum means a reference surface used to ensure that all elevation records are properly related. The current national datum is the National Geodetic Vertical Datum (NGVD) of 1929, which is expressed in relation to mean sea level, or the North American Vertical Datum (NAVD) of 1988.

Development means any man-made change to improved or unimproved real estate, including, but not limited to buildings or other structures, mining, dredging, filling, grading, paving, excavating, drilling operations, or storage of materials or equipment.

Elevated building means a non-basement building built to have the lowest floor elevated above the ground level by means of fill, solid foundation perimeter walls, pilings, columns (posts and piers), shear walls, or breakaway walls.

Encroachment means the advance or infringement of uses, plant growth, fill, excavation, buildings, permanent structures or development into a floodplain, which may impede or alter the flow capacity of a floodplain.

Existing Construction means any structure for which the "start of construction" commenced before the adoption of Springfield Flood Damage Ordinance 247, August 3, 1981.

Existing manufactured home park or subdivision means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including at a minimum the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) is completed before the effective date of the floodplain management regulations adopted by a community before the adoption of Springfield Flood Damage Ordinance 247, August 3, 1981.

Expansion to an existing manufactured home park or subdivision means the preparation of additional sites by the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads).

Flood or flooding means:

(a) A general and temporary condition of partial or complete inundation of normally dry land areas from:

a) **(1)** The overflow of inland or tidal waters; **or**

b) **(2)** The unusual and rapid accumulation or runoff of surface waters from any source.

(b) The collapse or subsidence of land along a shore of a lake or other body of water as the result of erosion or undermining caused by waves or currents of water exceeding anticipated cyclical levels or suddenly caused by an unusually high water level in a natural body of water, accompanied by a severe storm or by an unanticipated force of nature, such as a flash flood or an abnormal tidal surge or by some similarly unusual and unforeseeable event which results in flooding as defined in paragraph (a)(1) of this definition.

Flood Boundary and Floodway Map (FBFM) means the official map on which the Federal Emergency Management Agency (FEMA) or Federal Insurance Administration (FLA) has delineated the areas of flood hazards and regulatory floodway.

Flood Hazard Boundary Map (FHBM) means an official map of a community, issued by FEMA, where the boundaries of the areas of special flood hazard have been identified as Zone A.

Flood Insurance Rate Map (FIRM) means an official map of a community, on which FEMA has delineated both the areas of special flood hazard and the risk premium zones applicable to the community.

Flood Insurance Study (FIS) is the official hydraulic & hydrologic report provided by FEMA. The study contains an examination, evaluation and determination of flood hazards and corresponding water surface elevations. ~~The study may also report~~ contains flood profiles, as well as the FIRM, FHBM (where applicable) and other related data and information ~~the water surface elevation of the base flood.~~

Floodplain means any land area susceptible to flooding.

Floodplain management means the operation of an overall program of corrective and preventive measures for reducing flood damage and preserving and enhancing, where possible, natural resources in the floodplain, including but not limited to emergency preparedness plans, flood control works, floodplain management regulations, and open space plans.

Floodplain Management Administrator is the individual appointed to administer and enforce the City's floodplain management regulations.

Floodplain management regulations means this ordinance and other zoning ordinances, subdivision regulations, building codes, health regulations, special purpose ordinances, and other applications of police power which control development in flood-prone areas. This term describes federal, state or local regulations in any combination thereof, which provide standards for preventing and reducing flood loss and damage.

Floodproofing means any combination of structural and non-structural additions, changes, or adjustments to structures, which reduce or eliminate flood damage to real estate or improved real property, water and sanitary sewer facilities, structures and their contents.

Floodway means the channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one foot.

Floodway fringe means that area of the floodplain on either side of the regulatory floodway where encroachment may be permitted without additional hydraulic and/or hydrologic analysis.

Freeboard means the additional height, usually expressed as a factor of safety usually expressed in feet above a flood level for purposes of flood plain management. Freeboard tends to compensate for many unknown factors, such as wave action, blockage of bridge or culvert openings, and hydrological effect of urbanization of the watershed, which could contribute to flood heights greater than the heights calculated for a selected frequency flood and floodway conditions.

Free of obstruction means that any type of lower area enclosure or other construction element will not obstruct the flow of velocity water and wave action beneath the lowest horizontal structural member of the lowest floor of an elevated building during a base flood event. The requirement applies to the structures in V-Zones.

Functionally dependent facility means a facility which cannot be used for its intended purpose unless it is located or carried out in close proximity to water, such as a docking or port facility necessary for the loading and unloading of cargo or passengers, shipbuilding, ship repair, or seafood processing facilities. The term does not include long-term storage, manufacture, sales, or service facilities.

Hardship (as related to variances of this ordinance) means the exceptional hardship associated with the land that would result from a failure to grant the requested variance. The *City Commission of Springfield, Florida* requires that the variance is exceptional, unusual, and peculiar to the property involved. Mere economic or financial hardship alone is NOT exceptional. Inconvenience, aesthetic considerations, physical handicaps, personal preferences, or the disapproval of one's neighbors likewise cannot, as a rule, qualify as an exceptional hardship. All of these problems can be resolved through other means without granting a variance, even if the alternative is more expensive, or requires the property owner to build elsewhere or put the parcel to a different use than originally intended.

Highest adjacent grade means the highest natural elevation of the ground surface, prior to the start of construction, next to the proposed walls of a building.

Historic Structure means any structure that is:

- a) Listed individually in the National Register of Historic Places (a listing maintained by the Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register;
- b) Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic or a district preliminarily determined by the Secretary to qualify as a registered historic district;
- c) Individually listed on a state inventory of historic places in states with historic preservation programs which have been approved by the Secretary of the Interior; or
- d) Individually listed on a local inventory historic places in communities with historic preservation programs that have been certified either:
 1. By an approved state program as determined by the Secretary of the Interior, or
 2. Directly by the Secretary of the Interior in states without approved programs.

~~**Increased Cost of Compliance (ICC)** means the cost to repair a "substantially" or "repetitively" flood-damaged building that is required to bring it into compliance with the requirements of this ordinance. ICC coverage is provided for in every standard NFIP flood insurance policy.~~

Lowest adjacent grade means the lowest elevation, after the completion of construction, of the ground, sidewalk, patio, deck support, or basement entryway immediately next to the structure.

Lowest floor means the lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, used solely for parking of vehicles, building access, or storage, in an area other than a basement, is not considered a building's lowest floor, provided that such enclosure is not built so as to render the structure in violation of the non-elevation design standards of this ordinance.

Manufactured home means a building, transportable in one or more sections, which is built on a permanent chassis and designed to be used with or without a permanent foundation when connected to the required utilities. The term also includes park trailers, travel trailers, and similar transportable structures placed on a site for 180 consecutive days or longer and intended to be improved property.

Manufactured home park or subdivision means a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale.

Market value means the building value, excluding the land (as agreed to between a willing buyer and seller), as established by what the local real estate market will bear. Market value can be established by independent certified appraisal, replacement cost depreciated by age of building (Actual Cash Value), or adjusted assessed values.

Mean Sea Level means the average height of the sea for all stages of the tide. It is used as a reference for establishing various elevations within the floodplain. For purposes of this ordinance, the term is synonymous with National Geodetic Vertical Datum (NGVD).

National Geodetic Vertical Datum (NGVD) as corrected in 1929 is a vertical control used as a reference for establishing varying elevations within the floodplain.

New Construction means any structure for which the "start of construction" commenced on or after the adoption of Springfield Flood Damage Ordinance 247, August 3, 1981. The term also includes any subsequent improvements to such structures. ~~For flood insurance rates, structures for which the start of construction commenced on or after the effective date of the date of an initial FIRM or after December 31, 1974, whichever is later.~~

New manufactured home park or subdivision means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including at a minimum, the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) is completed on or after the effective date of the first floodplain management code, ordinance or standard.

North American Vertical Datum (NAVD) of 1988 means a vertical control used as a reference for establishing varying elevations within the floodplain.

~~**Obstruction** includes, but is not limited to, any dam, wall, wharf, embankment, levee, dike, pile, abutment, protection, excavation, channelization, bridge, conduit, culvert, building, wire, fence, rock, gravel, refuse, fill structure, vegetation or other material in, along, across or projecting into any watercourse which may alter, impede, retard or change the direction and/or velocity of the flow of water, or due to its location, its propensity to snare or collect debris carried by the flow of water, or its likelihood of being carried downstream.~~

Principally above ground means that at least 51 percent of the actual cash value of the structure is above ground.

Public safety and nuisance means anything which is injurious to safety or health of an entire community or neighborhood, or any considerable number of persons, or unlawfully obstructs the free passage or use, in the customary manner, of any navigable lake, or river, bay, stream, canal, or basin.

Reasonably safe from flooding means base flood waters will not inundate the land or damage structures and that any subsurface waters related to the base flood will not damage existing or proposed buildings.

Recreational vehicle means a vehicle that is:

- a) Built on a single chassis;
- b) 400 square feet or less when measured at the largest horizontal projection;
- c) Designed to be self-propelled or permanently towable by a light duty truck; and
- d) Designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use.

Regulatory floodway means the channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one foot.

Repetitive Loss means flood-related damages sustained by a structure on two separate occasions during a 10-year period ending on the date of the event for which the second claim is made, in which the cost of repairing the flood damage, on the average, equaled or exceeded 25% of the market value of the building at the time of each such flood event.

Special flood hazard area (SFHA) (see Area of Special Flood Hazard) means an area having special flood hazard and shown on a FHBM or FIRM as Zone A, AO, A1-A30, AE, A99, AH, V1-V30, VE, or V.

Start of construction (for other than new construction or substantial improvements under the Coastal Barrier Resources Act P. L. 97-348), includes substantial improvement, and means the date the building permit was issued, provided the actual start of construction, repair, reconstruction, or improvement was

within 180 days of the permit date. The actual start means the first placement of permanent construction of a building (including a manufactured home) on a site, such as the pouring of slabs or footings, installation of piles, construction of columns, or any work beyond the stage of excavation or placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading and Oiling; nor does it include the installation of streets and/or walkways; nor does it include excavation for a basement, footings, piers or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main building. For substantial improvement, the actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

Structure means all walled and roofed buildings, including gas or liquid storage tanks and manufactured homes that are principally above ground.

Substantial damage means damage of any origin sustained by a structure whereby the cost of restoring the structure to its before damaged condition would equal or exceed 50 percent of the market value of the structure before the damage occurred.

Substantial improvement means any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds 50 percent of the market value of the structure before the "start of construction" of the improvement. This term also includes structures that have incurred "substantial damage" or "repetitive loss", regardless of the actual repair work performed. This term does not, however, include any repair or improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications, which have been identified by the local code enforcement official prior to the application for the permit for improvement and which are the minimum necessary to assure safe living conditions. **This term does not include any alteration of a historic structure, provided that the alteration will not preclude the structure's continued designation as a historic structure.** ~~This includes any combination of repairs, reconstruction, rehabilitation, addition, alteration, or other improvements to a building taking place during a 5 year period, in which the cumulative cost of such improvements equals or exceeds 50 percent of the market value of the building either: (1) Before the improvement is started; or (2) — In case of substantial damage, before the damage occurred. For the purposes of this definition "substantial improvement" is considered to occur when the first alteration of any wall, ceiling, floor, or other structural part of the building commences, whether or not that alteration affects the external dimensions of the structure.~~

Substantially improved existing manufactured home parks or subdivisions is where the repair, reconstruction, rehabilitation or improvement of the streets, utilities and pads equals or exceeds 50 percent of the value of the streets, utilities and pads before the repair, reconstruction or improvement commenced.

Variance is a grant of relief from the requirements of this ordinance, which permits construction in a manner otherwise prohibited by this ordinance where specific enforcement would result in a hardship.

Violation means the failure of a structure or other development to be fully compliant with this ordinance. A structure or other development without the elevation certificate, other certifications, or other evidence of compliance required in this ordinance is presumed to be in violation until such time as that documentation is provided.

Watercourse means a lake, river, creek, stream, wash, channel or other topographic feature on or over which waters flow at least periodically. Watercourse includes specifically designated areas in which substantial flood damage may occur.

Water surface elevation means the height, in relation to the National Geodetic Vertical Datum (NGVD) of 1929, (or other datum, where specified) of floods of various magnitudes and frequencies in the floodplains of coastal or riverine areas.

ARTICLE 3. GENERAL PROVISIONS.

SECTION A. LANDS TO WHICH THIS ORDINANCE APPLIES.

This ordinance shall apply to all areas of special flood hazard within the zoning and building code jurisdiction of the City Commission of the City of Springfield, Bay County, Florida.

SECTION B. BASIS FOR ESTABLISHING THE AREAS OF SPECIAL FLOOD HAZARD.

The areas of special flood hazard identified by the Federal Emergency Management Agency in the Flood Insurance Study (FIS) for the City of Springfield, Bay County, Florida, dated **June 2, 2009** September 18, 2002, with the accompanying maps and other supporting data, and any subsequent revisions thereto, are adopted by reference and declared to be a part of this ordinance. **The FIS and FIRM are on file at the office of the City Clerk at City Hall.**

SECTION C. DESIGNATION OF FLOOD DAMAGE PREVENTION ORDINANCE ADMINISTRATOR

The City Commission of the City of Springfield, Bay County, Florida hereby appoints the City Clerk of the City of Springfield or the City Clerk's Appointed Agent to administer and implement the provisions of this ordinance and is herein referred to as the Floodplain Ordinance Administrator, the Floodplain Management Administrator, or the Administrator.

SECTION D. ESTABLISHMENT OF DEVELOPMENT PERMIT.

A development permit shall be required in conformance with the provisions of this ordinance prior to the commencement of any development activities.

SECTION E. COMPLIANCE.

No structure or land shall hereafter be located, extended, converted or structurally altered without full compliance with the terms of this ordinance and other applicable regulations.

SECTION F. ABROGATION AND GREATER RESTRICTIONS.

This ordinance is not intended to repeal, abrogate, or impair any existing easements, covenants, or deed restrictions. However, where this ordinance and another conflict or overlap, whichever imposes the more stringent restrictions shall prevail.

SECTION G. INTERPRETATION.

In the interpretation and application of this ordinance all provisions shall be:

- (1) Considered as minimum requirements;
- (2) Liberally construed in favor of the governing body, and
- (3) Deemed neither to limit nor repeal any other powers granted under state statutes.

SECTION H. WARNING AND DISCLAIMER OF LIABILITY.

The degree of flood protection required by this ordinance is considered reasonable for regulatory purposes and is based on scientific and engineering consideration. Larger floods can and will occur on rare occasions. Flood heights may be increased by man-made or natural causes. This ordinance does not imply that land outside the areas of special flood hazard or uses permitted within such areas will be free from flooding or flood damages. This ordinance shall not create liability on the part of City Commission of the City of Springfield, Bay County, Florida or by any officer or employee thereof for any flood damages that result from reliance on this ordinance or any administrative decision lawfully made thereunder.

SECTION I. PENALTIES FOR VIOLATION.

Violation of the provisions of this ordinance or failure to comply with any of its requirements, including violation of conditions and safeguards established in connection with grants of variance or special exceptions, shall constitute a **non-criminal violation** misdemeanor. Any person who violates this ordinance or fails to comply with any of its requirements shall, upon **adjudication** conviction thereof, be fined not more than \$300.00 or imprisoned for not more than 60 days, or both, and in addition, shall pay all costs and expenses involved in the case. Each day such violation continues shall be considered a separate offense. Nothing herein contained shall prevent the Floodplain Management Administrator from taking such other lawful actions as is necessary to prevent or remedy any violation.

ARTICLE 4. ADMINISTRATION.

SECTION A. PERMIT PROCEDURES.

Application for a Development Permit shall be made to the Floodplain Management Administrator on forms furnished by him or her prior to any development activities, and may include, but not be limited to, the following plans in duplicate drawn to scale showing the nature, location, dimensions, and elevations of the area in question; existing or proposed structures, earthen fill, storage of materials or equipment, drainage facilities, and the location of the foregoing. Specifically, the following information is required:

- (1) Application Stage:
 - a) Elevation in relation to mean sea level of the proposed lowest floor (including basement) of all buildings;
 - b) Elevation in relation to mean sea level to which any non-residential building will be flood-proofed;
 - c) Certificate from a registered professional engineer or architect that the non-residential flood-proofed building will meet the flood-proofing criteria in **Article 4, Section A(2) and** Article 5, Section B (2) and ~~Section D-(2)~~; and
 - d) Description of the extent to which any watercourse will be altered or relocated as result of proposed development; **and**
 - e) **Elevation in relation to mean sea level of the bottom of the lowest horizontal structural member of the lowest floor and provide a certification from a registered engineer or architect indicating that they have developed or reviewed the structural designs, specifications and plans of the construction and certify that they are in accordance with accepted standards of practice in Coastal High Hazard Areas.**

- (2) Construction Stage:

Upon placement of the lowest floor **or lowest horizontal structural member**, or flood-proofing by whatever construction means, it shall be the duty of the permit holder to submit to the Floodplain Management Administrator a certification of the NGVD **or NAVD** elevation of the lowest floor or flood-proofed elevation, **or bottom of the lowest horizontal structural member of the lowest floor** as built, in relation to mean sea level. Said certification shall be prepared by or under the direct supervision of a registered land surveyor or professional engineer and certified by same. When flood proofing is utilized for a particular building said certification shall be prepared by or under the direct supervision of a professional engineer or architect and certified by same. Any work undertaken prior to submission of the certification shall be at the permit holder's risk. (The Floodplain Management Administrator shall review the lowest floor and flood-proofing elevation survey data submitted.) The permit holder immediately and prior to further progressive work being permitted to proceed shall correct deficiencies detected by such review. Failure to submit the survey or failure to make said corrections required hereby shall be cause to issue a stop-work order for the project.

SECTION B. DUTIES AND RESPONSIBILITIES OF THE FLOODPLAIN MANAGEMENT ADMINISTRATOR.

Duties of the Administrator shall include, but are not be limited to:

- (1) Review permits to assure sites are reasonably safe from flooding.
- (2) Review all development permits to assure that the permit requirements of this ordinance have been satisfied;
- (3) Advise permittee that additional federal, state, or local permits may be required, and if such additional permits are necessary, require that copies of such permits be provided and maintained on file with the development permit;
- (4) Notify adjacent communities, the State NFTP Coordinator, and other federal and/or state agencies with statutory or regulatory authority prior to any alteration or relocation of a watercourse;
- (5) Assure that maintenance is provided within the altered or relocated portion of said watercourse so that the flood-carrying capacity is not diminished;
- (6) Verify and record the actual elevation (in relation to mean sea level) of the lowest floor (A-Zones) or bottom of the lowest horizontal structural member of the lowest floor (V-Zones) of all new or substantially improved buildings, in accordance with Article 5, Section B(1) and (2) and Section E(2), respectively ~~4, Section A (2)~~;
- (7) Verify and record the actual elevation (in relation to mean sea level) to which the new or substantially improved buildings have been flood-proofed, in accordance with Article 5, Section B (2) ~~4, Section A (2)~~;
- (8) Review certified plans and specifications for compliance. When floodproofing is utilized for a particular building, certification shall be obtained from a registered engineer or architect certifying that all areas of the building, together with all attendant utilities and sanitary facilities, below the required elevation are water tight with walls substantially impermeable to the passage of water, and use structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effects of buoyancy in compliance with Article 5, Section B(2) of this ordinance. In Coastal High Hazard Areas, certification shall be obtained from a registered professional engineer or architect that the building is designed and securely anchored to pilings or columns in order to withstand velocity waters and hurricane wave wash. Additionally in Coastal High Hazard Areas, if the area below the lowest horizontal structural member of the lowest floor is enclosed, it may be done so with open wood lattice and insect screening or with non-supporting breakaway walls that meet the standards of Article 5, Section E(6) of this ordinance;
- (9) Interpret the exact location of boundaries of the areas of special flood hazard. When there appears to be a conflict between a mapped boundary and actual field conditions, the Floodplain Management Administrator shall make the necessary interpretation. The person contesting the location of the boundary shall be given a reasonable opportunity to appeal the interpretation as provided in this article;
- (10) When base flood elevation data or floodway data have not been provided in accordance with Article 3, Section B, the Floodplain Management Administrator shall obtain, review and reasonably utilize any base flood elevation and floodway data available from a federal, state, or any other source, in order to administer the provisions of Article 5; and
- (11) Coordinate all change requests to the FIS and FIRM or FBFM or both with the requester, State, and FEMA.
- (12) Where Base Flood Elevation arc utilized, obtain and maintain records of lowest floor and flood-proofing elevations for new construction and substantial improvements.

ARTICLE 5. PROVISIONS FOR FLOOD HAZARD REDUCTION.

SECTION A. GENERAL STANDARDS. In all areas of special flood hazard, all development sites including new construction and substantial improvements shall be reasonably safe from flooding, and meet the following provisions shall apply:

- (1) New construction and substantial improvements shall be designed or modified and adequately anchored to prevent flotation, collapse or lateral movement of the structure resulting from hydrostatic and hydrodynamic loads, including the effects of buoyancy;
- (2) Manufactured homes shall be anchored to prevent flotation, collapse, or lateral movement. Methods of anchoring may include, but are not limited to, use of over-the-top or frame ties to ground anchors. This standard shall be in addition to and consistent with applicable state requirements for resisting wind forces;
- (3) New construction and substantial improvements shall be constructed with materials and utility equipment resistant to flood damage;
- (4) New construction or substantial improvements shall be constructed by methods and practices that minimize flood damage;
- (5) Electrical, heating, ventilation, plumbing, air conditioning equipment and other service facilities, including duct work, shall be designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding;
- (6) New and replacement water supply systems shall be designed to minimize or eliminate infiltration of flood waters into the system;
- (7) New and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of flood waters into the systems and discharges from the systems into flood waters;
- (8) On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during flooding;
- (9) Any alteration, repair, reconstruction or improvements to a building that is in compliance with the provisions of this ordinance shall meet the requirements of "new construction" as contained in this ordinance; and
- (10) Any alteration, repair, reconstruction or improvements to a building that is not in compliance with the provisions of this ordinance, shall be undertaken only if said non-conformity is not furthered, extended, or replaced.

SECTION B. SPECIFIC STANDARDS FOR A-ZONES.

In all A-Zones areas of special flood hazard where base flood elevation data have been provided, as set forth in Article 3, Section B, the following provisions, in addition to those set forth in Article 5, Section A, shall apply:

- (1) Residential Construction. New construction or substantial improvement of any residential building (or manufactured home) shall have the lowest floor, including basement, elevated at or above the base flood elevation. Should solid foundation perimeter walls be used to elevate a structure, there must be a minimum of two openings on different sides of each enclosed area sufficient to facilitate automatic equalization of flood hydrostatic forces on both sides of the exterior walls shall be provided in accordance with standards of Article 5, Section B (3).

- (2) Non-Residential Construction. New construction or substantial improvement of any commercial, industrial, or non-residential building (or manufactured home) shall have the lowest floor, including basement, elevated at or above the base flood elevation. Buildings located in all A-Zones may be flood-proofed in lieu of being elevated provided that all areas of the building components, **together with attendant utilities and sanitary facilities**, below the **base flood elevation corresponding to the BFB** plus one foot are water tight with walls substantially impermeable to the passage of water, and use structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effect of buoyancy. A registered professional engineer or architect shall certify that the standards of this subsection are satisfied. Such certification shall be provided to the **Floodplain Administrator will the corresponding engineering data and operational and maintenance plans** official as set forth in Article 6 Section C(9).
- (3) Enclosures below the Lowest Floor (Elevated Buildings). New construction or substantial improvements of elevated buildings that include fully enclosed areas formed by foundation and other exterior walls below the lowest floor elevation shall be designed to preclude finished living space and designed to allow for the entry and exit of floodwaters to automatically equalize hydrostatic flood forces on exterior walls.
- (a) Designs for complying with this requirement must either be certified by a professional engineer or architect or meet the following minimum criteria:
- (i) Provide a minimum of two openings having a total net area of not less than one square inch for every square foot of enclosed area subject to flooding;
 - (ii) The bottom of all openings shall be no higher than one foot above foundation interior grade (which must be equal to in elevation or higher than the exterior foundation grade); and
 - (iii) Openings may be equipped with screens, louvers, valves, or other coverings or devices provided they provide the required net area of the openings and permit the automatic flow of floodwaters in both directions.
- (b) **Fully enclosed areas below the lowest floor shall solely be used for parking of vehicles, storage and building access.** Access to the enclosed area shall be minimum necessary to allow for parking of vehicles (garage door) or limited storage of maintenance equipment used in connection with the premises (standard exterior door) or entry to the living area (stairway or elevator); and
- (c) The interior portion of such enclosed area shall not be partitioned or finished into separate rooms.
- (d) Where elevation requirements exceed 6 feet above the highest adjacent grade, a copy of the legally recorded deed restriction prohibiting the conversion of the area below the lowest floor to a use or dimension contrary to the building's originally approved design, shall be presented as a condition of issuance of the final Certificate of Occupancy.
- (4) Standards for Manufactured Homes and Recreational Vehicles.
- a) All manufactured homes placed, or substantially improved, on individual lots or parcels, **outside of an existing manufactured home park or subdivision**, in expansions to existing manufactured home parks or subdivisions, in a new manufactured home park or subdivision or in **an existing manufactured home park or subdivision on which a manufactured home has incurred substantial damage as the result of a flood, the lowest floor shall be elevated on a permanent foundation to no lower than one foot above the base flood elevation and be securely anchored to an adequately anchored foundation system to resist flotation, collapse and lateral movement.** ~~substantially improved manufactured home parks or subdivisions, must meet all the requirements for new construction, including~~

~~elevation and anchoring.~~ All manufactured homes placed or substantially improved in an existing manufactured home park or subdivision must be elevated so that:

- (i) The lowest floor of the manufactured home is elevated at or above the base flood elevation, or
 - (ii) The manufactured home chassis is supported by reinforced piers or other foundation elements of at least an equivalent strength, of no less than 36 inches in height above the grade.
 - (iii) The manufactured home must be securely anchored to the adequately anchored foundation system to resist flotation, collapse and lateral movement.
 - ~~(iv) In an existing manufactured home park or subdivision on which a manufactured home has incurred "substantial damage" as the result of a flood, any manufactured home placed or substantially improved must meet the standards of Article 5, Section B (4)(b)(i) and (iii) above.~~
- c) All recreational vehicles placed on sites must either:
- (i) Be on the site for fewer than 180 consecutive days,
 - (ii) Be fully licensed and ready for highway use (a recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities and security devices and has no permanently attached additions), or
 - (iii) Meet all the requirements for new construction, including anchoring and elevation requirements of Article 5, Section B (4)(a) or (b) ~~(i) and (iii)~~, above.

(5) Adequate drainage paths around structures shall be provided on slopes to guide water away from structures within Zone AH.

(6) Standards for waterways with established Base Flood Elevations, but without Regulatory Floodways. Located within the areas of special flood hazard established in Article 3, Section B, where streams exist for which base flood elevation data has been provided by FEMA without the delineation of the regulatory floodway (Zones AE and A1-30), the following provisions, in addition to those set forth in Article 5, Section B (1) through (4), shall apply:

(a) Until a regulatory floodway is designated, no new construction, substantial improvement or other development included fill shall be permitted within the areas of special flood hazard, unless it is demonstrated that the cumulative effect and anticipated development will not increase the water surface elevation of the base flood more than one foot at any point in the community.

(b) Development activities which increase the water surface elevation of the base flood by more than one foot may be allowed, provided that the developer or applicant first applies, with the City's endorsement, for a conditional FIRM revision, and receives the approval of FEMA.

~~(5)~~**(7) Floodways.** Located within areas of special flood hazard established in Article 3, Section B, are areas designated as floodways. Since the floodway is an

extremely hazardous area due to the velocity of flood waters which carry debris, potential projectiles and have significant erosion potential, the following provisions shall apply:

- a) Prohibit encroachments, including fill, new construction, substantial improvements and other developments unless certification (with supporting technical data) by a registered professional engineer is provided demonstrating through hydrologic and hydraulic analyses performed in accordance with standard engineering practices that encroachments shall not result in any increase in flood levels during occurrence of the base flood discharge;
 - b) If Article 5, Section B (5)(a) is satisfied, all new construction and substantial improvements shall comply with all applicable flood hazard reduction provisions of Article 5.
 - c) Prohibit the placement of manufactured homes (mobile homes), except in an existing manufactured homes (mobile homes) park or subdivision. A replacement manufactured home may be placed on a lot in an existing manufactured home park or subdivision provided the anchoring standards of Article 5, Section A (2), and the elevation standards of Article 5, Section B (1) and the encroachment standards of Article 5, Section B (5) (a), are met.
 - d) Development activities including new construction and substantial improvements that increase the water surface elevation of the base flood by more than one foot may be allowed, provided that the developer or applicant first applies, with the City's endorsement, for a conditional FIRM revision, and receives the approval of FEMA.
 - e) When fill is proposed, in accordance with the permit issued by the Florida Department of Health, within the regulatory floodway, the development permit shall be issued only upon demonstration by appropriate engineering analyses that the proposed fill will not increase the water surface elevation of the base flood in accordance with Article 5, Section B7a.
- (8) For all structures located seaward of the Coastal Construction Control Line (CCCL), the lowest floor of all new construction and substantial improvements shall be elevated at least one foot above the base flood elevation established by FEMA, as adopted by Article 3.B.

Notwithstanding the foregoing, but in addition thereto, for all habitable structures located seaward of the CCCL, the bottom of the lowest shore-parallel horizontal structural member of the lowest floor of all new construction and substantial improvements shall be elevated to the 100-year flood elevation established by the Florida Department of Environmental Protection (FDEP). For purposes of this subsection, habitable structure means structures which (i) are designed primarily for human occupancy and (ii) are potential locations for shelter from storms. Typically included are residences, hotels and restaurants. Typically excluded are bath houses, cabanas, swimming pools, garages and other structures which are either not designed primarily for human occupancy or, if designed for occupancy by humans, are not also potential locations for human shelter from storms.

SECTION C. STANDARDS FOR A-ZONES STREAMS WITHOUT ESTABLISHED BASE FLOOD ELEVATION AND FLOODWAYS.

Located within the areas of special flood hazard established in Article 3, Section B, where streams exist for which no base flood elevation data or regulatory floodway has been provided designated by the Federal Emergency Management Agency, the following provisions shall apply:

(1) Require standards of Article 5, Section A.

(2) Require that all new subdivision proposals and other proposed developments greater than fifty (50) lots or five (5) acres, whichever is the lesser, include within such proposals base flood elevation data. The standards set forth in Article 5, Section B shall apply.

- (3) (1)**—When base flood elevation data or floodway data have not been provided in Accordance with Article 3, Section B, the Administrator shall obtain, review, and reasonably utilize any base flood elevation and floodway data available from a federal, state, or any other source, in order to administer the provisions of Article 5. When such base flood elevation data is utilized:
- a) Obtain the elevation (in relation to the mean sea level) of the lowest floor (including the basement) of all new and substantially improved structures,
 - b) Obtain, if the structure has been floodproofed in accordance with the requirements of Section B (2) of this ordinance, the elevation in relation to the mean sea level to which the structure has been floodproofed, and
 - c) Maintain a record of all such information with the official designated in Article 3, Section C.
- (2)** **(4)** Notify, in riverine situations, adjacent communities and the State Coordinating Office prior to any alteration or relocation of a watercourse, and submit copies of such notifications to FBMA.
- (3)** **(5)** Assure that the flood carrying capacity within the altered or relocated portion of any watercourse is maintained.
- (4)** **(6)** Manufactured homes shall be installed using methods and practices that minimize flood damage. They must be elevated and anchored to prevent flotation, collapse, or lateral movement. Methods of anchoring may include, but are not limited to, use of over-the-top or frame ties to ground anchors. This requirement is in addition to applicable State and local anchoring requirements for resisting wind forces.
- (5)** **(7)** When the data is not available from any source as in paragraph **(3)** above, the lowest floor of the structure shall be elevated at or above the highest adjacent grade.

~~SECTION D. STANDARDS FOR STREAMS WITH ESTABLISHED BASE FLOOD ELEVATION WITHOUT REGULATORY FLOODWAYS.~~

~~Located within the areas of special flood hazard established in Article 3, Section B, where streams exist for which base flood elevation data has been provided by the Federal Emergency Agency without the delineation of the regulatory floodway, the following provisions shall apply:~~

~~Until a regulatory floodway is designated, no new construction, substantial improvements, or other development (including fill) shall be permitted within the areas of special flood hazard, designated as Zones A1-30 and AE on the FIRM, unless it is demonstrated that the cumulative effect of the proposed development, when combined with all other existing and anticipated development will not increase the water surface elevation of the base flood more than one foot at any point within the City of Springfield.~~

~~Development activities in Zones AI-30, AE, and AH, on the City of Springfield's FIRM which increase the water surface elevation of the base flood by more than one foot may be allowed, provided that the developer or applicant first applies with the City of Springfield's endorsement for a conditional FIRM revision, and receives the approval of the Federal Emergency Management Agency.~~

SECTION DE. STANDARDS FOR AO, AH and UNNUMBERED A ZONES

Located within the areas of special flood hazard established in Article 3, Section B, are areas designated as shallow flooding areas. These areas have flood hazards associated with base flood depths of one to three feet, where a clearly defined channel does not exist and the path of flooding is unpredictable and indeterminate; therefore, the following provisions apply:

- (1) All new construction and substantial improvements of residential structures shall have the lowest floor, including basement, elevated to or above **the highest adjacent grade at least as high as** the flood depth specified on the Flood Insurance Rate Map, ~~above the highest adjacent grade.~~ If no flood depth number is specified, the lowest floor, including basement, shall be elevated at or above the highest adjacent grade.
- (2) All new construction and substantial improvements of non-residential structures shall:
 - a) Have the lowest floor, including basement, elevated to or above the flood depth specified on the Flood Insurance Rate Map, above the highest adjacent grade. If no flood depth number is specified, the lowest floor, including basement, shall be elevated at least 2 feet above the highest adjacent grade, or
 - b) Together with attendant utility and sanitary facilities be completely flood-proofed to the specified flood level so that any space below that level is watertight with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads and effects of buoyancy. Certification is required as per Article S, Section B (2).
 - c) ~~In zones AO, AH, zones r~~Require drainage paths around structures on slopes to guide water away from structures.
 - d) ~~In unnumbered A-Zones, when base flood information is not available from a Federal, State, or other source, the lowest floor, including basement shall be elevated at least two feet above the highest adjacent grade.~~
- (3) Fully enclosed areas below the lowest floor that are subject to flooding shall meet the non-elevation design requirements of Article 5, Section B.**

SECTION EF. STANDARDS FOR SUBDIVISION PROPOSALS.

- (1) All subdivision proposals shall be consistent with the need to minimize flood damage;
- (2) All subdivision proposals shall have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize flood damage;
- (3) All subdivision proposals shall have adequate drainage provided to reduce exposure to flood hazards, and
- (4) Base flood elevation data shall be provided for subdivision proposals and other proposed development proposals (including manufactured home parks and subdivisions) that exceed fifty lots or five acres, whichever is the lesser.

SECTION FG. COASTAL HIGH HAZARD AREAS.

Located within areas of special flood hazard areas established in Article 3, Section B are Coastal High Hazard Areas, designated as Zones VI - V30, VE, or V. These areas have special flood hazards associated with high velocity waters from surges and, therefore, in addition to meeting all provisions in this ordinance, the following provisions shall also apply:

- (1) All new construction and substantial improvements in Zones VI - V30 and VE (V if base flood elevation is available) shall be elevated on pilings or columns so that:
 - a) The bottom of the lowest horizontal structural member of the lowest floor (excluding the pilings or columns) is elevated to one foot freeboard; and
 - b) The pile or column foundation and structure attached thereto is anchored to resist flotation, collapse, and lateral movement due to the effects of wind and water loads acting simultaneously on all building components. Wind and water loading values shall each have a one percent chance of being equaled or exceeded in any given year (one-percent annual chance).
 - c) **For all structures located seaward of the Coastal Construction Control Line (CCCL), the bottom of the lowest horizontal structural member of the lowest floor of all new construction and substantial improvements shall be elevated to at least one foot above the base flood elevation established by FEMA, as adopted by Article 3.B.**
 - d) **Notwithstanding the foregoing, but in addition thereto, for all habitable structures located seaward of the CCCL, the bottom of the lowest shore-parallel horizontal structural member of the lowest floor of all new construction and substantial improvements shall be elevated to the 100-year flood elevation established by the Florida Department of Environmental Protection (FDEP). For purposes of this subsection, habitable structure means structures which (i) are designed primarily for human occupancy and (ii) are potential locations for shelter from storms. Typically included are residences, hotels and restaurants. Typically excluded are bath houses, cabanas, swimming pools, garages and other structures which are either not designed primarily for human occupancy or, if designed for occupancy by humans, are not also potential locations for human shelter from storms.**
- e) A registered professional engineer or architect shall develop or review the structural design, specifications and plans for the construction, and shall certify that the design and methods of construction to be used are in accordance with accepted standards of practice for meeting the provisions of paragraph G (1).
- f) Obtain the elevation (in relation to mean sea level) of the bottom of the lowest horizontal structural member of the lowest floor (excluding pilings and columns) of all new and substantially improved structures in Zones VI - V30 and VE. The Floodplain Management Administrator shall maintain a record of all such information.
- g) All new construction shall be located landward of the reach of mean high tide.

- h) Provide that all new construction and substantial improvements have the space below the lowest floor either free of obstruction or constructed with non-supporting breakaway walls, open wood-lattice work, or insect screening intended to collapse under wind and water loads without causing collapse, displacement, or other structural damage to the elevated portion of the building or supporting foundation system. For the purpose of this section, a breakaway Avail shall have design safe loading resistance of not less than 10 and no more than 20 pounds per square foot. Use of breakaway walls which exceed a design safe loading resistance of 20 pounds per square foot (either by design or when so required by local codes) may be permitted only if a registered professional engineer or architect certifies that the designs proposed meet the following conditions:
- a) Breakaway wall collapse shall result from water load less than that which would occur during the base flood; and
 - b) The elevated portion of the building and supporting foundation system shall not be subject to collapse, displacement, or other structural damage due to the effects of wind and water loads acting simultaneously on all building components (structural and nonstructural). Maximum wind and water loading values to be used in this determination shall each have a one percent chance of being equaled or exceeded in any five year.
- (6) The enclosed space below the lowest floor shall be useable solely for parking of vehicles, building access, or storage. Such space shall not be partitioned into multiple rooms, temperature-controlled, or used for human habitation.
- (7) Prohibit the use of fill for structural support of buildings. When fill is proposed in a coastal high hazard area, appropriate engineering analyses shall be conducted to evaluate the impacts of the fill prior to issuance of a development permit.
- (8) Prohibit man-made alteration of sand dunes and mangrove stands that would increase potential flood damage.
- (9) All manufactured homes to be placed or substantially improved within Zones VI - V30, V, and VE on the City of Springfield's FIRM on sites meet the standards of Article 5, Section F (1) through (8) and that manufactured homes placed or substantially improved on other sites in an existing manufactured home park or subdivision with Zones VI - V30, V, and VE on the FIRM meet the requirements of Article 5, Section B (4) (a) through (b), if they are located:
- a) Outside of a manufactured home park or subdivision,
 - b) In a new manufactured home park or subdivision,
 - c) In an expansion to an existing manufactured home park or subdivision, or
 - d) In an existing manufactured home park or subdivision in which a manufactured home has incurred "substantial damage" as the result of a flood.
 - e) Prohibit the placement of manufactured homes (mobile home), except in an existing manufactured homes (mobile homes) park or subdivision. A replacement manufactured home may be placed on a lot in an existing manufactured home park or subdivision provided the anchoring standards of Article 5, Section G, and the elevation standards of Article 5, Section O (1) and the encroachment standards of Article S, Section G are met.
- (10) Recreational vehicles placed on sites within Zones VI - V30, V, and VE on the community's FIRM either;
- a) Be on the site for fewer than 180 consecutive days,
 - b) Be fully licensed and ready for highway use, on its wheels or jacking system, is attached to the site only by quick disconnect type utilities and security devices, and has no permanently attached additions; or

- c) Meet the requirements of Article 4, Section B (Permit Procedures) and Article 5, Section B and Section F.
- d) Prohibit the placement of recreational vehicles, except in an existing recreational vehicle park. Must be fully licensed and ready for highway use, on its wheels or jacking system, is attached to the site by quick disconnect type utilities and security devices, and has no permanently attached additions. Be on site no more than 180 days and park must have a plan for removal in case of a flooding threat.

SECTION GH. CRITICAL FACILITIES.

Construction of new critical facilities shall be, to the extent possible, located outside the limits of the special flood hazard area (SFHA).

ARTICLE 6. VARIANCE PROCEDURES.

SECTION A. DESIGNATION OF VARIANCE AND APPEALS BOARD.

The Springfield Planning Board as established by the City Commission of the City of Springfield, Bay County, Florida shall hear and decide appeals and requests for variances from Uie requirements of this ordinance.

SECTION B. DUTIES OF VARIANCE AND APPEALS BOARD.

The board shall hear and recommend to the City Commission for a final decision appeals when it is alleged an error in any requirement, decision, or determination is made by the Floodplain Management Administrator in the enforcement or administration of this ordinance. Any person aggrieved by the decision of the board may appeal such decision to the appropriate court, as provided by Florida Statutes.

SECTION C. VARIANCE PROCEDURES.

In acting upon such applications, the Springfield Planning Board shall consider all technical evaluations, all relevant factors, standards specified in other sections of this ordinance, and:

- (1) The danger that materials may be swept onto other lands to the injury of others;
- (2) The danger of life and property due to flooding or erosion damage;
- (3) The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owner
- (4) The importance of the services provided by the proposed facility to the community;
- (4) The necessity to the facility of a waterfront location, where applicable;
- (5) The availability of alternative locations for the proposed use which are not subject to flooding or erosion damage;
- (6) The compatibility of the proposed use with existing and anticipated development;
- (7) The relationship of the proposed use to the comprehensive plan and floodplain management program for that area;
- (8) The safety of access to the property in times of flood for ordinary and emergency vehicles;
- (9) The expected heights, velocity, duration, rate of rise, and sediment of transport of the flood waters and the effects of wave action, if applicable, expected at the site; and

- (10) The costs of providing governmental services during and after flood conditions, including maintenance and repair of public utilities and facilities such as sewer, gas, electrical, and water systems, and streets and bridges.

SECTION D. CONDITIONS FOR VARIANCES.

- (1) Variances shall only be issued when there is:
 - a) A showing of good and sufficient cause;
 - b) A determination that failure to grant the variance would result in exceptional hardship; and
 - c) A determination that the granting of a variance will not result in increased flood heights, additional threats to public expense, create nuisance, cause fraud on or victimization of the public, or conflict with existing local laws or ordinances.
- (2) Variances shall only be issued upon a determination that the variance is the minimum necessary deviation from the requirements of this ordinance.
- (3) Any applicant to whom a variance is granted shall be given written notice specifying the difference between the base flood elevation and the elevation to which the lowest floor is to be built and stating that the cost of flood insurance will be commensurate with the increased risk resulting from the reduced lowest floor elevation (See Article 6, Section E).
- (4) Variances shall not be granted after-the-fact.
- (5) The Floodplain Management Administrator shall maintain the records of all appeal actions and report any variances to the Federal Emergency Management Agency upon request (See Article 6, Section E).

SECTION E. VARIANCE NOTIFICATION.

Any applicant to whom a variance is granted shall be given written notice over the signature of a community official that:

- (1) The issuance of a variance to construct a structure below the base flood elevation will result in increased premium rates for flood insurance up to amounts as high as \$25 for \$100 of insurance coverage, and
- (2) Such construction below the base flood level increases risks to life and property.

A copy of the notice shall be recorded by the Floodplain Management Administrator in the Office of the Bay County Clerk of Courts Public Records and shall be recorded in a manner so that it appears in the chain of title of the affected parcel of land.

The Floodplain Management Administrator will maintain a record of all variance actions, including justification for their issuance, and report such variances issued in its biennial report submitted to the Federal Emergency Management Agency.

SECTION F. HISTORIC STRUCTURES.

Variances may be issued for the repair or rehabilitation of "historic" structures - meeting the definition in this ordinance - upon a determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a historic structure.

SECTION G. SPECIAL CONDITIONS.

Upon consideration of the factors listed in Article 6, and the purposes of this ordinance, the Springfield Planning Board may attach such conditions to the granting of variances, as it deems necessary to further the purposes of this ordinance.

SECTION H. STRUCTURES IN REGULATORY FLOODWAY.

Variations shall not be issued within any designated floodway if any impact in flood conditions or increase in flood levels during the base flood discharge would result.


ARTICLE 7. SEVERABILITY.

If any section, clause, sentence, or phrase of the Ordinance is held to be invalid or unconstitutional by any court of competent jurisdiction, then said holding shall in no way effect the validity of the remaining portions of this Ordinance.

Effective Date: This ordinance will take effect upon passage.


6th **PASSED, APPROVED AND ADOPTED** in regular session of the City Commission on this the July day of July, 2009.

CITY OF SPRINGFIELD, FLORIDA



Robert E. Walker, Mayor

ATTEST:



Teresa Cox, City Clerk

First Reading: June 1st, 2009

Date Published: June 22nd, 2009

Second Reading: July 6th, 2009

